Signing & Striping

NUMBER	ITEMS	NOT REQ'D	NOT DONE	SATISFIED	Location in Standards
1	Must be included in the Paving plan set	☐	☐	☐	
2	COG general notes for Signing & Striping	☐	☐	☐	0.6.6, 2.1.4(B.10.c), 2.1.5(A), 2.1.10,Ex No 2
3	Traffic Study establishing speeds/lanes	☐	☐	☐	2.1.2(A.3)
4	Design Speed of Street(s)	☐	☐	☐	4.1.3(E.5), 4.1.3(H.2.c)
5	Scale 1"=40'	☐	☐	☐	4.6.4(A.2)
6	Signing/Striping Legend on every sheet	☐	☐	☐	
7	Typ st section w/ striping included in sec	☐	☐	☐	
8	Same as Paving geometry	☐	☐	☐	
9	Show approved streetlights/T. signals	☐	☐	☐	
10	Signing & Striping call-outs	☐	☐	☐	G-3208
11	Show and label all existing signs type and identify to remove or remain	☐	☐	☐	4.6.4(C.3), 4.6.4(C.4)
12	Existing/Proposed Average Daily Traffic of Street(s)	☐	☐	☐	
13	End of roadway barriers	☐	☐	☐	
14	Show RPMs	☐	☐	☐	4.6.3(C.2), 4.6.4(D.2)
15	Show entire length of project in plan view	☐	☐	☐	4.6.4(A.3)
16	Show min. 300' beyond match existing	☐	☐	☐	4.6.4(A.4)
	Show & label ex striping & make light linetype	☐	☐	☐	
17	street name signs	☐	☐	☐	4.1.2(A), 4.6.3(B.6), G-3248
18	Sign locations stationed and MUTCD designation with size noted	☐	☐	☐	4.6.4(C.2)
19	No Parking signs(R8-3A) 350' to 400' spacing (R7-9a w/Bike Lane) 12"x18" w/ other reg signs 24"x24" stand alone	☐	☐	☐	0.6.6(J), 4.6.3(B.3), G-3252-2
20	R4-7 w/ OM1-3 at median bullnose	☐	☐	☐	

REVIEW #
BY DATE

Revised 6/5/2008

NUMBER	ITEMS	NOT REQ'D	NOT DONE	SATISFIED	Signing & Striping REVIEW # ____ BY ____ DATE ____ Location in Standards
21	Lane Only signs w/lane indicator plaque (Except at tee intersections)	☐	☐	☐	
22	Stop signs: 36" Art., 30" Coll., none on local	☐	☐	☐	
23	Warning signs: 36" Arterial, 30" Collector distance per	☐	☐	☐	Table 2C-4 MUTCD
24	Center lane 2-way left, 4 signs per mile, not on speed limit signs	☐	☐	☐	
25	Speed limit signs 4 per mile (R2-1)	☐	☐	☐	4.6.3(B.4)
26	1st speed limit sign 330' from intersection	☐	☐	☐	
27	Advance street name signs on Arterials in the medians	☐	☐	☐	4.6.3(B.7)
28	Bike Lane w/signing and symbols at 1000' spacing	☐	☐	☐	G-3252
29	Only break bike lane strips/edge line at high volume driveways	☐	☐	☐	Per City Traffic Eng
30	End bike lane/edge line 50' before intersections without rt. Turn lane	☐	☐	☐	Per City Traffic Eng
31	Striping dimensioned off C/L and/or F/C and lengths or stations provided	☐	☐	☐	4.6.4(D.4)
32	Dbl. Arrow (W1-7) @ Coll./Coll. & Coll./Art. T-intersections	☐	☐	☐	
33	Crosswalks at stop/signal controlled ONLY	☐	☐	☐	
34	Stop Bar, 24" All locations	☐	☐	☐	
35	Deceleration Lanes	☐	☐	☐	4.1.4(F)
36	Merge taper lengths and signing (15:1)	☐	☐	☐	G-3214
37	Turn lanes w/arrows & "ONLY" legend	☐	☐	☐	G-3208
38	Turn Lane storage lengths, Art= 250' min Coll= 75' min	☐	☐	☐	G-3208
39	Opening length, right turn lane 15:1 for straight curb taper, left turn lane 100' min	☐	☐	☐	G-3208
40	Dimensions shall be to face of curb	☐	☐	☐	