EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. LOVE LMAUNT DATE 9/7/2013	AGENCY 60014 EAR	<u> </u>
DATE 9/7/2013	TIME 0021	
<i>i</i>	OCATION 10701 5	
(n) 1. Ensure that gas tank is attached to instrument and	· ·	
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. 0.2°C 2. Intoxilyzer 8000 display reads "PUSH BUTTON" 3. Go to the "Control Testing Menu". Select "D" for made press ENTER. 4. Air blank completed. 5. Calibration check completed. Test results 0. 6. Air blank completed. 7. Remove printed record. Attach the record to the constant of the constan	AC, into a clean dry simulator furn on the simulator and allow temper D START" for wet control for wet control for LAC.	ature to reach 34°C ±
•		

DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000

Location: 10701 S ESTRELLA PKW

Serial Number: 80-000312 Core Version: 8105.48

09/07/2013

00:21:02

Standard Lot#: 32012100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	00:21:35
0.100 Cal Check	0.098	00:21:56
Air Blank	0.000	00:22:25

Preventative Maintenance Performed -- Timer Reset